LANGAN

Memorandum

300 Kimball Drive Parsippany, NJ 07054 T: 973.560.4900 F: 973.560.4901

To: Michael DeCarlo, Township of Verona Engineering Manager

From: Timothy Derrick, P.E.

Michael Fowler, P.E.

Info: Chris Gengaro, President - Montclair Golf Club

David Kupstas, General Manager - Montclair Golf Club

Michael Campbell, Director of Golf Course Operations - Montclair Golf Club

Date: 11 December 2019

Re: Stormwater Calculations Summary

Tennis Courts Renovation

Montclair Golf Club Verona, New Jersey

Langan Project No.: 001039209

This technical memorandum was prepared to demonstrate that the requirements of the Stormwater Management Rule (NJAC 7:8) and Chapter 123 (Stormwater Management) of the Township of Verona Code for the renovation of the tennis courts at Montclair Golf Club (the Club) have been met. The memorandum, calculations, plans, and figures demonstrate that flows from the project area decrease due to a decrease of impervious coverage (0.23 acres) by eliminating a tennis court and tennis court practice area and therefore meet the requirements of the regulations listed above.

The proposed work includes:

- Removal of the 7 existing tennis courts and tennis practice area;
- Construction of 6 new tennis courts;
- Re-grading of the upper portion of the existing golf practice range;
- Re-sodding and installing underdrains in the lower portion of the golf practice range; and
- The reconstruction of areas affected by the improvements listed above.

The Club previously obtained a permit from the Hudson Essex Passaic Soil Conservation District for this work. The project is considered a "major development" because the work will disturb greater than 1 acre of land. Major developments are required to meet the requirements for stormwater quality, stormwater quantity, and groundwater recharge as described in the Stormwater Management Rule. How the project meets the stormwater quality, groundwater recharge, and stormwater quantity is described below and demonstrated in the attached calculations.

Stormwater Quality

Per 7:8-5.5 (a) of the Stormwater Management Rule and Section 123-9.G.(1) of the Township of Verona Code, "Stormwater management measures shall only be required for water quality control if an additional one-quarter acre of impervious surface is being proposed on a

Technical Memorandum

Stormwater Calculations Summary
Tennis Courts Renovation
Montclair Golf Club
Verona, New Jersey
Langan Project No.: 001039209
11 December 2019 - Page 2 of 3

development site." Stormwater quality measures are not required for this project because the impervious surface will decrease by 0.23 acres within the project area as shown in the attached calculations and plans.

Groundwater Recharge

In order to meet groundwater recharge requirements per 7:8-5.4(a)2.i. of the Stormwater Management Rule and Section 123-9.F.(1)(b)[1] of the Township of Verona Code, the design engineer must either demonstrate that either:

- The site maintains 100% of the average annual preconstruction groundwater recharge volume for the site; or
- Demonstrate that the increase or stormwater runoff volume for the two-year storm is infiltrated.

However, as shown on the attached soils map, the existing soil is "D type" soils. D type soils do not provide any existing infiltration and therefore there is no groundwater recharge to be compensated for and the project will maintain the average annual preconstruction groundwater recharge volume. The New Jersey Groundwater Recharge Spreadsheet has been provided to demonstrate the lack of recharge.

Stormwater Quantity

7:8-5.4(a)3 of the Stormwater Management Rule and Section 123-9.F.(1)(c) of the Township of Verona Code allows a project to meet the requirement of the rule/code in one of 3 ways. The project meets the requirements through method 1:

 Demonstrate through hydrologic and hydraulic analysis that for stormwater leaving the site, post-construction runoff hydrographs for the 2-, 10-, and 100-year storm events do not exceed, at any point in time, the preconstruction runoff hydrographs for the same storm events;

The project does not increase the amount of stormwater leaving the site for the 2-, 10-, and 100-year storm events as described in item 1 above. Below is a summary of our hydraulic analysis for the project.

The project has two drainage areas: one area (Watershed A) that drains to a catch basin located in Prospect Avenue and the remaining area (Watershed B) that drains to the golf course. Table 1 demonstrates that the flow from Watershed A decreases for the 2-, 10-, and 100-year storm events. The flow from the project area (Watershed B) will also decrease because the area decreases and the CN value decreases as shown on the enclosed CN calculation sheet and on the watershed area plans.



Technical Memorandum

Stormwater Calculations Summary Tennis Courts Renovation Montclair Golf Club Verona, New Jersey Langan Project No.: 001039209 11 December 2019 - Page 3 of 3

Table 1 - Comparison of Existing and Proposed Peak Discharges										
	Watershed A									
	2-year Flow (cfs)	10-year Flow (cfs)	100-year Flow (cfs)							
Existing	5.501	8.933	15.53							
Proposed	5.246	8.741	15.47							
Difference	-0.255	-0.192	-0.06							

Timothy B. Derrick, P.E.

N.J. Professional Engineer License No. 4678200

N.J. Professional Engineer License No. 3239800

NJ Certificate of Authorization No. 24GA27996400 \\langan.com\\data\\PAR\\data2\001039209\\Project Data_Discipline\Site Civil\Stormwater\\Report Text\\Tennis Courts\2019.12.10 - MGC Tennis Court Renovation Stormwater Memo.docx

WATERSHED AREA PLANS

HYDROLOGIC ANALYSIS

Project Montcla	ir Golf Club - Tennis Court Reconstruction			EAJ	Date		
	ip of West Orange, Essex County, NJ			LM	Date		
Circle one:	Present Developed	Existing WS A (Tennis Courts)					
1. Runoff Curve	Number (CN)						
Soil Name	Cover description				Area	Product	
and	(cover type, treatment, and		CN 1			of	
hydrologic	hydrologic condition;	7	33	4	x acres	CN x area	
group	percent impervious;	e 2-	2-	. 2-4	mi ²		
	unconnected/connected impervious	Table	Fig.	Fig.	%		
(Appendix A)	area ratio)						
D	IMPERVIOUS	98			1.21	118.58	
D	Grass (Good)	80			0.59	47.20	
D	Woods (Poor)	77			0.06	4.62	
1 Use only one CN	source per line	1	otals	=	1.86	170.40	
CN (weighted) =	total product = 170.40	_ =	91	.61	Use CN =	92	
J (total area						
	1.00						

Project Montcla	ir Golf Club - Tennis Court Reconstruction			TD	Date	12/10/2019		
	ip of West Orange, Essex County, NJ			•	Date			
Circle one:	Present Developed	Existing WS B (Practice Range)						
1. Runoff Curve	Number (CN)							
Soil Name	Cover description				Area	Product		
and	(cover type, treatment, and		CN 1			of		
hydrologic	hydrologic condition;	2	33	-4	x acres	CN x area		
group	percent impervious;	e 2-	2-	. 2	mi ²			
	unconnected/connected impervious	Table	Fig.	Fig.	ુ %			
(Appendix A)	area ratio)							
D	IMPERVIOUS	98			0.07	6.86		
D	Grass (Good)	80			0.59	47.20		
D	Woods (Poor)	77			0.09	6.93		
1 Use only one CN	source per line	1	otals	=	0.75	60.99		
CN (weighted) =	total product = 60.99	_ =	81	.32	Use CN =	81		
ch (weighted) -								
	0.75					L		

Project Montcla	ir Golf Club - Tennis Court Reconstruction			EAJ	Date		
-	ip of West Orange, Essex County, NJ			LM	Date		
Circle one:	Present Developed	Proposed WS A (Tennis Courts)					
1. Runoff Curve	Number (CN)						
Soil Name	Cover description				Area	Product	
and	(cover type, treatment, and		CN 1			of	
hydrologic	hydrologic condition;	-2	3	4	x acres	CN x area	
group	percent impervious;	2	. 2-	. 2-4	mi²		
	unconnected/connected impervious	Table	Fig.	Fig.	Olo Olo		
(Appendix A)	area ratio)						
D	IMPERVIOUS	98			1.03	100.94	
D	Grass (Good)	80			0.79	63.20	
D	Woods (Poor)	77			0.06	4.62	
1 Use only one CN	source per line	T	otals	=	1.88	168.76	
CN (weighted) =	total product = 168.76 total area	- =	89	.77	Use CN =	90	
	1.88						

oject Montc	lair Golf Club - Tennis Court Reconstruction	_		LM	Date	
	Present Developed		P	ropose	d WS B (Practice	Range)
Soil Name and hydrologic group	Cover description (cover type, treatment, and hydrologic condition; percent impervious; unconnected/connected impervious	Table 2-2	Fig. 2-3 NO	Fig. 2-4	Area acres mi² %	Produc of CN x ar
(Appendix A)	area ratio) IMPERVIOUS	98			0.02	1.96
D	Grass (Good)	80			0.61	48.80
D	Woods (Poor)	77			0.09	6.93
Use only one Ci	N source per line	Т	otals	=	0.72	57.69
CN (weighted)	=total product =57.69	_ =	80	.13	Use CN =	80

Tennis Court Hydrologic Calculations.gpw

Hydraflow Table of Contents

Tuesday, 12 / 10 / 2019 Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020 2 - Year Summary Report...... 1 Hydrograph Reports...... 2 Hydrograph No. 1, SCS Runoff, EX WSHD A...... 2 10 - Year Summary Report...... 4 Hydrograph Reports...... 5 Hydrograph No. 1, SCS Runoff, EX WSHD A...... 5 Hydrograph No. 2, SCS Runoff, PR WSHD A...... 6 100 - Year Summary Report...... 7 Hydrograph Reports...... 8 Hydrograph No. 1, SCS Runoff, EX WSHD A...... 8

Hydrograph No. 2, SCS Runoff, PR WSHD A......9

Hydrograph Summary Report
Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description		
1	SCS Runoff	5.501	1	727	17,826				EX WSHD A		
2	SCS Runoff	5.246	1	727	16,702				PR WSHD A		
4											
8											
							na na		e		
T						,:					
									9		
1									*		
Ī									=		
								e	a ^p		
I											
									*		
							^				
				9							
								×			
-		20									
						2)					
4											
7											
									, š		
				, ,	×						
Те	Tennis Court Hydrologic Calculations.gpw					Return Period: 2 Year			Tuesday, 12 / 10 / 2019		

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Tuesday, 12 / 10 / 2019

Hyd. No. 1

EX WSHD A

= 5.501 cfsPeak discharge = SCS Runoff Hydrograph type = 12.12 hrs Time to peak Storm frequency = 2 yrs = 17,826 cuft Hyd. volume Time interval = 1 min = 92 Curve number Drainage area = 1.860 ac

Basin Slope = 0.0 % Hydraulic length = 0 ft
Tc method = User Time of conc. (Tc) = 6.00 min
Total precip. = 3.42 in Distribution = Custom



Hyd No. 2

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Tuesday, 12 / 10 / 2019


Hyd. No. 2

PR WSHD A

Storm duration

= 5.246 cfsPeak discharge = SCS Runoff Hydrograph type = 12.12 hrs Time to peak = 2 yrs Storm frequency = 16,702 cuft Hyd. volume Time interval = 1 min = 90 Curve number = 1.880 ac

Drainage area = 0 ftHydraulic length = 0.0 %Basin Slope Time of conc. (Tc) $= 6.00 \, \text{min}$ = User Tc method Distribution = Custom = 3.42 inTotal precip.



Hydrograph Summary Report
Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

		- Injuranom rijeragi aprila								
lyd. lo.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description	
1	SCS Runoff	8.933	1	727	29,902				EX WSHD A	
2	SCS Runoff	8.741	1	727	28,707				PR WSHD A	
		-				à				
			ii							
				\$1						
									,	
					9					
Те	ennis Court H	ydrologic (Calculati	ons.gpw	Return f	Period: 10	Year	Tuesday, 1	2 / 10 / 2019	
_										

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Tuesday, 12 / 10 / 2019

Hyd. No. 1


EX WSHD A

= 8.933 cfsPeak discharge Hydrograph type = SCS Runoff $= 12.12 \, hrs$ Time to peak = 10 yrsStorm frequency Hyd. volume = 29,902 cuft = 1 min Time interval Curve number = 92 = 1.860 acDrainage area

Basin Slope = 0.0 % Hydraulic length = 0 ft

Tc method = User Time of conc. (Tc) = 6.00 min

Total precip. = 5.21 in Distribution = Custom



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

= 5.21 in

Tuesday, 12 / 10 / 2019

= Custom


Hyd. No. 2

PR WSHD A

Total precip.

= 8.741 cfsPeak discharge Hydrograph type = SCS Runoff Time to peak $= 12.12 \, hrs$ Storm frequency = 10 yrsHyd. volume = 28,707 cuft Time interval = 1 min Curve number = 90 = 1.880 acDrainage area Hydraulic length = 0 ftBasin Slope = 0.0 % Time of conc. (Tc) $= 6.00 \, \text{min}$ = User Tc method

Distribution



Hydrograph Summary Report Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

yd. o.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	15.53	1	727	53,940				EX WSHD A
2	SCS Runoff	15.47	1	727	52,820				PR WSHD A
			ık.				×		
			,						
					-				
									,
				5:			٠		s .
								. v	А
									4
									*.
	-		~					o	
۷									,
						7.			*
						, a			
	*								e
Те	nnis Court Hy	drologic (Calculati	ons.gpw	Return F	Period: 100	Year	Tuesday, 1	2 / 10 / 2019


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Tuesday, 12 / 10 / 2019

Hyd. No. 1

EX WSHD A

Hydrograph type= SCS RunoffPeak discharge= 15.53 cfsStorm frequency= 100 yrsTime to peak= 12.12 hrsTime interval= 1 minHyd. volume= 53,940 cuftDrainage area= 1,860 acCurve number= 92



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Tuesday, 12 / 10 / 2019

Hyd. No. 2


PR WSHD A

= 15.47 cfsPeak discharge Hydrograph type = SCS Runoff Time to peak = 12.12 hrs Storm frequency = 100 yrs= 52,820 cuft Hyd. volume Time interval = 1 min Curve number = 90 = 1.880 ac Drainage area

Basin Slope = 0.0 % Hydraulic length = 0 ft
Tc method = User Time of conc. (Tc) = 6.00 min
Total precip. = 8.71 in Distribution = Custom



NRCS SOILS MAP



NEW JERSEY GROUNDWATER RECHARGE SPREADSHEET

Montclair Golf Club **New Jersey** Annual Groundwater Recharge Analysis (based on GSR-32) **Project Name:** Groundwater Recharge Annual P Climatic Description: **Short Game Practice Area** Spreadsheet Select Township | (in) Factor Version 2.0 November 2003 **Analysis Date:** 09/17/19 **ESSEX CO., VERONA BORO** 48.9 1.67 **Post-Developed Conditions Pre-Developed Conditions** Annual Annual Annual Annual Land Land Area Area TR-55 Land Cover Soil TR-55 Land Cover Soil Recharge Recharge Recharge Recharge (acres) Segment (acres) Segment (in) (cu.ft) (in) (cu.ft) **Urban Land*** 1.28 Impervious areas **Urban Land*** 0.0 1.05 Impervious areas 0.0 0.16 Woods **Urban Land*** 2 0.16 Woods **Urban Land*** 0.0 0.0 **Urban Land*** 1.17 Open space **Urban Land*** 1.4 Open space 0.0 0.0 5 9 10 10 11 11 12 12 13 13 14 14 15 15 Total Total Total Total Annual Annual Annual Annual Total = 2.6 Total = 2.6 Recharge Recharge Recharge Recharge (cu-ft) (cu.ft) (in) (in) 0.0 Annual Recharge Requirements Calculation | 0.0 Total Impervious 45,738 100% Area (sq.ft) Procedure to fill the Pre-Development and Post-Development Conditions Tables % of Pre-Developed Annual Recharge to Preserve = 0 Post-Development Annual Recharge Deficit= (cubic feet) For each land segment, first enter the area, then select TR-55 Land Cover, then select Soil. Start from the top of the table Recharge Efficiency Parameters Calculations (area averages) and proceed downward. Don't leave blank rows (with A=0) in between your segment entries. Rows with A=0 will not be DRWC= 0.00 RWC= 0.00 (in) displayed or used in calculations. For impervious areas outside of standard lots select "Impervious Areas" as the Land Cover. (in) ERWC = 0.00 EDRWC= 0.00 (in) Soil type for impervious areas are only required if an infiltration facility will be built within these areas

